

Appl. No.: 09/540,952
Amdt. dated February 18, 2004
Reply to Office action of November 19, 2003

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently amended) A method of monitoring the performance of a program being executed on a computer system, comprising:
- executing the program on a computer system, the program having object code instructions;
 - at intervals interrupting execution of the program, including delivering a first interrupt; and
 - in response to at least a subset of the first interrupts, determining measuring a latency of a particular object code instruction, storing the latency in a first database, the particular object code instruction being executed by the computer such that the program remains unmodified.
2. (Currently amended) The method of claim 1 wherein ~~said determining~~ measuring the latency includes:
- determining an initial value of a cycle counter;
 - performing the particular object code instruction;
 - determining a final value of the cycle counter; and
 - ~~determining~~ measuring the latency based on the initial value and the final value.
3. (Original) The method of claim 2 further comprising:
- executing at least one instruction selected from the set consisting of (A) an instruction for ensuring that the particular object code instruction is performed after the initial value of the cycle counter is determined, and (B) an instruction for ensuring that the particular object code instruction is performed before the final value of the cycle counter is determined.

Appl. No.: 09/540,952
Amdt. dated February 18, 2004
Reply to Office action of November 19, 2003

4. (Original) The method of claim 2 further comprising:
applying an adjustment to the final value.
5. (Cancelled).
6. (Original) The method of claim 1 wherein the particular object code instruction has a variable execution time.
7. (Original) The method of claim 1 wherein the particular object code instruction is a memory access instruction.
8. (Original) The method of claim 1 wherein the computer system includes a plurality of memory units, each memory unit of the plurality of memory units having a different range of access times, and further comprising:
associating the particular object code instruction with a memory unit in accordance with the latency and the range of access times for the memory unit.
9. (Currently amended) The method of claim 1 wherein said ~~determining~~ measuring the latency includes:
determining an initial value of a cycle counter;
executing a first dependent instruction to provide a predetermined execution order;
performing the particular object code instruction;
executing a second dependent instruction to provide the predetermined execution order;
determining a final value of the cycle counter; and
determining the latency based on the initial value and the final value.
10. (Original) The method of claim 9 wherein the first and second dependent instructions are memory barrier instructions.

Appl. No.: 09/540,952
Amdt. dated February 18, 2004
Reply to Office action of November 19, 2003

11. (Currently amended) The method of claim 1 wherein said ~~determining~~
measuring includes:

identifying at least one issue block of instructions; and
interpreting the instructions of the at least one issue block;
wherein said particular object code instruction is in the issue block.

12. (Original) The method of claim 11 wherein said interpreting emulates a
machine language instruction set of the computer system.

13. (Original) The method of claim 11 wherein said interpreting updates a
state of the interrupted program as though each interpreted instruction had been
directly executed by the computer system.

B 14. (Currently amended) A computer program product for sampling latency of
a computer program having object code instructions while the object code
instructions are executing without modifying the computer program, the computer
program product for use in conjunction with a computer system, the computer
program product comprising a computer readable storage medium and a
computer program mechanism embedded therein, the computer program
mechanism comprising:

one or more instructions to deliver interrupts at intervals during execution
of the program, including delivering a first interrupt;

one or more instructions to ~~determine~~ measure a latency of a particular
object code instruction; and

one or more instructions to, in response to at least a subset of the first
interrupts, store the latency value for the particular object code instruction in a first
database.

15. (Currently amended) The computer program product of claim 14 wherein
said one or more instructions to ~~determine~~ measure the latency value include
instructions to:

Appl. No.: 09/540,952
Amdt. dated February 18, 2004
Reply to Office action of November 19, 2003

determine an initial value of a cycle counter;
perform the particular object code instruction;
determine a final value of the cycle counter; and
| ~~determine-measure~~ the latency based on the initial value and the final
value.

16. (Original) The computer program product of claim 14 further comprising at least one instruction selected from the set consisting of (A) an instruction for ensuring that the particular object code instruction is performed after the initial value of the cycle counter is determined, and (B) an instruction for ensuring that the particular object code instruction is performed before the final value of the cycle counter is determined.

17. (Original) The computer program product of claim 15 further comprising one or more instructions to apply an adjustment to the final value.

18. (Cancelled).

19. (Original) The computer program product of claim 14 wherein the particular object code instruction has a variable execution time.

20. (Original) The computer program product of claim 14 wherein the particular object code instruction is a memory access instruction.

21. (Original) The computer program product of claim 14 wherein the computer system includes a plurality of memory units, each memory unit of the plurality of memory units having a different range of access times, and further comprising one or more instructions that associate the particular object code instruction with a memory unit in accordance with the latency value and the range of access times for the memory unit.

Appl. No.: 09/540,952
Amdt. dated February 18, 2004
Reply to Office action of November 19, 2003

22. (Currently amended) The computer program product of claim 14 wherein said one or more instructions to ~~determine~~measure the latency value include:

one or more instructions to determine an initial value of a cycle counter;
a first dependent instruction to provide a predetermined execution order;
the particular object code instruction;
a second dependent instruction to provide the predetermined execution order;

one or more instructions to determine a final value of the cycle counter;
and

one or more instructions to ~~determine~~measure the latency value based on the initial value and the final value.

23. (Original) The computer program product of claim 22 wherein the first and second dependent instructions are memory barrier instructions.

24. (Currently Amended) The computer program product of claim 14 wherein said instructions to ~~determine~~measure include:

one or more instructions that identify at least one issue block of instructions; and

an interpreter to interpret the instructions of the at least one issue block;
wherein said particular object code instruction is in the issue block.

25. (Original) The computer program product of claim 24 wherein the interpreter emulates a machine language instruction set of the computer system.

26. (Original) The computer program product of claim 24 wherein the interpreter updates a state of the interrupted program as though each interpreted instruction had been directly executed by the computer system.

27. (Currently amended) A computer system comprising:
a processor for executing instructions; and

Appl. No.: 09/540,952
Amdt. dated February 18, 2004
Reply to Office action of November 19, 2003

a memory storing instructions including:

one or more instructions to deliver interrupts at intervals during execution of the program, including delivering a first interrupt;

one or more instructions to ~~determine~~-measure a latency of a particular object code instruction; and

one or more instructions to, in response to at least a subset of the first interrupts, store the latency value for the particular object code instruction in a first database.

28. (Currently Amended) The computer system of claim 27 wherein said one or more instructions to ~~determine~~-measure the latency value include instructions to:

determine an initial value of a cycle counter;

perform the particular object code instruction;

determine a final value of the cycle counter; and

~~determine~~-measure the latency based on the initial value and the final value.

29. (Original) The computer system of claim 27 wherein the memory further comprises at least one instruction selected from the set consisting of (A) an instruction for ensuring that the particular object code instruction is performed after the initial value of the cycle counter is determined, and (B) an instruction for ensuring that the particular object code instruction is performed before the final value of the cycle counter is determined.

30. (Original) The computer system of claim 28 wherein the memory further comprises one or more instructions to apply an adjustment to the final value.

31. (Cancelled).

Appl. No.: 09/540,952

Amdt. dated February 18, 2004

Reply to Office action of November 19, 2003

32. (Original) The computer system of claim 27 wherein the particular object code instruction has a variable execution time.

33. (Original) The computer system of claim 27 wherein the particular object code instruction is a memory access instruction.

34. (Original) The computer system of claim 27 further comprising:
a plurality of memory units, each memory unit of the plurality of memory units having a different range of access times, and
wherein the memory further comprises one or more instructions that associate the particular object code instruction with a memory unit in accordance with the latency value and the range of access times for the memory unit.

B 35. (Currently amended) The computer system of claim 27 wherein said one or more instructions to ~~determine~~measure the latency value include:

one or more instructions to determine an initial value of a cycle counter;

a first dependent instruction to provide a predetermined execution order;

the particular object code instruction;

a second dependent instruction to provide the predetermined execution order;

one or more instructions to determine a final value of the cycle counter;

and

one or more instructions to ~~determine~~measure the latency value based on the initial value and the final value.

36. (Original) The computer system of claim 36 wherein the first and second dependent instructions are memory barrier instructions.

37. (Currently amended) The computer system of claim 27 wherein said instructions to ~~determine~~measure include:

Appl. No.: 09/540,952
Amtd. dated February 18, 2004
Reply to Office action of November 19, 2003

one or more instructions that identify at least one issue block of instructions; and

an interpreter to interpret the instructions of the at least one issue block; wherein said particular object code instruction is in the issue block.

B1
38. (Original) The computer system of claim 37 wherein the interpreter emulates a machine language instruction set of the computer system.

39. (Original) The computer system of claim 37 wherein the interpreter updates a state of the interrupted program as though each interpreted instruction had been directly executed by the computer system.
